

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:1A AC,DC
- 2.Voltage rating:100V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:30mΩMax.
- 5.Insulation resistance:500MΩMin.
- 6.Withstanding voltage:300V AC/minute
- 7.Material:Nylon 66 UL 94V-0
Shell:0.15mm Copper
- 8.Bill Of Part No.:
FU1004H-XP-X-HF

Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green
.	.
.	.
.	.

9.Ordering Information & Dimensions

30	29.00	29.50
20	19.00	23.50
14	13.00	17.50
8	7.00	11.50
PIN	A	B

TOLERANCE

X.	X.XXX ±0.10
X.X ±0.30	
X.XX ±0.20	Angular ±2°



UNIT:
mm

DWG TYPE.

Customer Drawing

PART NO.

FU1004H-XP-HF

DRAWING NO.

C-FU1004H-XP-HF

APPROVED BY

CHECKED BY

DRAWN BY

PAGE 1OF1

REV.

SCALE 1: 1

A

A		FOR NEW DRAWING	GuobaoLi	2017.12.02
REV.	ECN NO	REVISION RECORD	DRAW	DATE

1

2

3

4

5

6 QMI-P12-05-05