

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:1A AC,DC
- 2.Voltage rating:50V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:30mΩMax.
- 5.Insulation resistance:100MΩMin.
- 6.Withstanding voltage:500V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU1254H-XP-X-HF


Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green

9.Ordering Information & Dimensions

17.50	8.25	19.90	15	8.75	6.25	11.15	8
16.25	8.25	18.65	14	7.50	6.25	9.90	7
15.00	8.25	17.40	13	6.25	6.25	8.65	6
13.75	8.25	16.15	12	5.00	4.25	7.40	5
12.50	8.25	14.90	11	3.75	4.25	6.15	4
11.25	8.25	13.65	10	2.50	3.00	4.90	3
10.00	6.25	12.40	9	1.25	2.00	3.65	2
A	B	C	PIN	A	B	C	PIN

TOLERANCE

X.	X.XXX ±0.1
X.X ±0.30	
X.XX ±0.20	Angular ±2°



UNIT:
mm

DWG TYPE.

Customer Drawing

PART NO.

FU1254H-XP-X-HF

DRAWING NO.

C-FU1254H-XP-X-HF

APPROVED BY

CHECKED BY

DRAWN BY

PAGE

1OF1

REV.

SCALE

10: 1

A

8		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE