

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:1A AC,DC
- 2.Voltage rating:50V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:40mΩMax.
- 5.Insulation resistance:100MΩMin.
- 6.Withstanding voltage:500V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU1501H-XP-X-HF

Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green

9.Ordering Information & Dimensions

18.00	21.00	13	9.00	12.00	7
16.50	19.50	12	7.50	10.50	6
15.00	18.00	11	6.00	9.00	5
13.50	16.50	10	4.50	7.50	4
12.00	15.00	9	3.00	6.00	3
10.50	13.50	8	1.50	4.50	2
A	B	PIN	A	B	PIN

TOLERANCE		PART NO.		东莞市福朗连接器制造有限公司						
X. X.XXX ±0.1		FU1501H-XP-X-HF		DongGuan FuLang Connector Manufacturing Co., LTD						
X.X ±0.30		DRAWING NO.		TITLE. 1.25mm PITCH WIRE TO BOARD HOUSING						
X.XX ±0.20 Angular ±2°										
	UNIT:	APPROVED BY		CHECKED BY		DRAWN BY		PAGE		REV.
	mm							10F1		
DWG TYPE.								SCALE		A
Customer Drawing								10: 1		

8		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE