

RoHS

## CUST INFORMATION.

| PART NO. | DRAWING NO. | REV. |
|----------|-------------|------|
| NA       | NA          | NA   |

### Specifications:

- 1.Current rating:2A AC,DC
- 2.Voltage rating:125V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:10mΩMax.
- 5.Insulation resistance:1000MΩMin.
- 6.Withstanding voltage:1000V AC/minute
- 7.Material:Nylon 66 UL94V-0
- 8.Bill Of Part No.:

FU2006H-XP-X-HF


| Pin: | Material Color |
|------|----------------|
| 2    | A : White      |
| 3    | B : Black      |
| 4    | C : Red        |
| .    | D : Orangr     |
| .    | E : Yellow     |
| .    | F : Green      |
| .    | .              |
| .    | .              |
| .    | .              |

### 9.Ordering Information & Dimensions

| Pin | Dim(mm) |      |      | Pin | Dim(mm) |      |      |
|-----|---------|------|------|-----|---------|------|------|
|     | A       | B    | C    |     | A       | B    | C    |
| 2   | 6.0     | 2.0  | 4.8  | 9   | 20.0    | 16.0 | 18.8 |
| 3   | 8.0     | 4.0  | 6.8  | 10  | 22.0    | 18.0 | 20.8 |
| 4   | 10.0    | 6.0  | 8.8  | 11  | 24.0    | 20.0 | 22.8 |
| 5   | 12.0    | 8.0  | 10.8 | 12  | 26.0    | 22.0 | 24.8 |
| 6   | 14.0    | 10.0 | 12.8 | 13  | 28.0    | 24.0 | 26.8 |
| 7   | 16.0    | 12.0 | 14.8 | 14  | 30.0    | 26.0 | 28.8 |
| 8   | 18.0    | 14.0 | 16.8 | 15  | 32.0    | 28.0 | 30.8 |

### TOLERANCE

|            |             |
|------------|-------------|
| X.         | X.XXX ±0.10 |
| X.X ±0.30  |             |
| X.XX ±0.20 | Angular ±2° |



UNIT:  
mm

DWG TYPE.

Customer Drawing

### PART NO.

FU2006H-XP-X-HF

### DRAWING NO.

C-FU2006H-XP-X-HF

APPROVED BY

CHECKED BY

DRAWN BY

PAGE 1OF1

REV.

SCALE 1: 1

A

| A    |        | For New Drawing | GuobaoLi | 2017.12.06 |
|------|--------|-----------------|----------|------------|
| REV. | ECN NO | REVISION RECORD | DRAW     | DATE       |

