

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:3A AC,DC
- 2.Voltage rating:100V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:10mΩMax.
- 5.Insulation resistance:1000MΩMin.
- 6.Withstanding voltage:800V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU2501H-XP-X-HF

Pin: Material Color
2 A : White
3 B : Black
4 C : Red
. D : Orangr
. E : Yellow
. F : Green
.
.
.

9.Ordering Information & Dimensions

PIN	A	B	PIN	A	B
2	2.50	5.70	12	27.50	30.70
3	5.00	8.20	13	30.00	33.20
4	7.50	10.70	14	32.50	35.70
5	10.00	13.20	15	35.00	38.20
6	12.50	15.70	16	37.50	40.70
7	15.00	18.20	17	40.00	43.20
8	17.50	20.70	18	42.50	45.70
9	20.00	23.20	19	45.00	48.20
10	22.50	25.70	20	47.50	50.70
11	25.00	28.20			

TOLERANCE		PART NO.	东莞市福朗连接器制造有限公司 DongGuan FuLang Connector Manufacturing Co., LTD		
X.	X.XXX ±0.1	FU2501H-XP-X-HF	DRAWING NO.		
X.X ±0.30			C-FU2501H-XP-X-HF	TITLE.	
X.XX ±0.20	Angular ±2°			2.5mm Pitch Wire To Board Housing	
	UNIT: mm	APPROVED BY	CHECKED BY	DRAWN BY	PAGE 1 OF 1
DWG TYPE.					REV. A
Customer Drawing					SCALE 5: 1

A		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE