

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:3A AC,DC
- 2.Voltage rating:100V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:20mΩMax.
- 5.Insulation resistance:1000MΩMin.
- 6.Withstanding voltage:800V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU2502H-XP-X-HF


Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green
.	.
.	.

9.Ordering Information & Dimensions

PIN	A	B	PIN	A	B
2	2.50	7.00	9	20.00	24.50
3	5.00	9.50	10	22.50	27.00
4	7.50	12.00	11	25.00	29.50
5	10.00	14.50	12	27.50	32.00
6	12.50	17.00	13	30.00	34.50
7	15.00	19.50	14	32.50	37.00
8	17.50	22.00	15	35.00	39.50

TOLERANCE

X.	X.XXX ±0.1
X.X ±0.30	
X.XX ±0.20	Angular ±2°



UNIT:
mm

DWG TYPE.

Customer Drawing

PART NO.

FU2502H-XP-X-HF

DRAWING NO.

C-FU2502H-XP-X-HF

APPROVED BY

CHECKED BY

DRAWN BY

PAGE

1OF1

REV.

SCALE

5: 1

A

东莞市福朗连接器制造有限公司
DongGuan FuLang Connector Manufacturing Co., LTD

TITLE.

2.5mm Pitch Wire To Board Housing

A		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE

QMI-P17-06-05